

HL Heavy Duty Lead Screw Precision Dovetail Slides



Standard Features

Precision Lead Screw · Graduated Micrometer Dial · Balanced Crank Handle · Thrust Bearings
Rugged Construction · Lubrication on All Sizes · Greater Flexibility and Stability

MODEL	SLIDE WIDTH	CARRIER HEIGHT	SLIDE HEIGHT	AVAILABLE LENGTHS				WEIGHT PER INCH OF CAST IRON	
				CARRIER		BASE		CARRIER	BASE
				MINIMUM	MAXIMUM	MINIMUM	MAXIMUM		
HL-4	4"	1.38"	2.125"	4"	36"	4"	60"	.98 lbs.	1.13 lbs.
HL-6	6"	2.00"	2.875"	6"	36"	6"	60"	2.50 lbs.	1.86 lbs.
HL-8	8"	2.00"	3.125"	8"	36"	8"	60"	3.18 lbs.	3.16 lbs.

▶ 1/2-20 "V" Type or 1/2-10 Acme Lead Screw on H4 Slides

▶ 5/8-20 "V" Type or 5/8-10 Acme Lead Screw on H6 Slides

▶ 3/4-20 "V" Type or 3/4-10 Acme Lead Screw on H8 Slides

Accessories

Gib Lock Handles · Way Wipers · Knurled Knob · Accordion Type or Steel Covers
Tapered Gib · Anti-Backlash Nut · Nickel Plating · Compounding · Right Angle Drive
Hand Wheels



MILWAUKEE
SLIDE AND
SPINDLE

FAMCO MACHINE DIVISION

BELCO INDUSTRIES, INC.

1001-31st STREET

KENOSHA, WISCONSIN 53140

PHONE NO.: 1-262-654-3516

FAX NO.: 1-262-654-0803

e-mail: SALES@FAMCOMACHINE.COM