

RBL Heavy Duty Recessed Base Lead Screw Precision Dovetail Slides



Standard Features

Precision Lead Screw with Lubricated Bronze Nut • Graduated Micrometer Dial • Thrust Bearings
Balanced Crank Handle • Lubrication on All Sizes • For Higher Loads, Low Speeds

MODEL	SLIDE WIDTH	CARRIER HEIGHT	SLIDE HEIGHT	AVAILABLE LENGTHS				WEIGHT PER INCH OF CAST IRON	
				CARRIER		BASE		CARRIER	BASE
				MINIMUM	MAXIMUM	MINIMUM	MAXIMUM		
RBL-3	3"	1.00"	1.750"	3"	18"	3"	30"	.57 lbs.	.62 lbs.
RBL-4	4"	1.62"	2.250"	4"	36"	4"	60"	1.00 lbs.	1.05 lbs.
RBL-6	6"	2.00"	3.000"	6"	36"	6"	72"	2.50 lbs.	1.69 lbs.
RBL-8	8"	2.00"	3.250"	8"	36"	8"	72"	3.16 lbs.	2.93 lbs.
RBL-10	10"	2.81"	3.750"	10"	36"	10"	72"	4.80 lbs.	3.66 lbs.
RBL-12	12"	2.43"	4.000"	12"	36"	12"	72"	5.77 lbs.	5.27 lbs.
RBL-16	16"	3.25"	5.000"	16"	60"	16"	100"	9.47 lbs.	9.10 lbs.
RBL-20	20"	3.87"	6.000"	20"	60"	20"	100"	14.43 lbs.	13.58 lbs.
RBL-24	24"	4.50"	7.000"	24"	60"	24"	100"	20.37 lbs.	18.93 lbs.

- ▶ 5/16-40 "V" Type Lead Screw on RB-3 Slides
 - ▶ 1/2-20 "V" Type or 1/2-10 Acme Lead Screw on RB-4 Slides
 - ▶ 5/8-20 "V" Type or 5/8-10 Acme Lead Screw on RB-6 Slides
 - ▶ 3/4-10 Acme Lead Screw on RB-8 Slides
 - ▶ 1"-10 Acme Lead Screw on RB-10 and RB-12 Slides
 - ▶ 1-1/4"-10 Acme Lead Screw on RB-16 and RB-20 Slides
 - ▶ 1-1/2"-10 Acme Lead Screw on RB-24 Slides

Accessories

Rigid Base with Wide Mounting Flanges • Way Wipers • Gib Lock Handles • Tapered Gib
Right Angle Drive • T-Slots • Nickel Plating • Compounding • Knurled Knob



MILWAUKEE
SLIDE AND
SPINDLE

FAMCO MACHINE DIVISION

BELCO INDUSTRIES, INC.
1001-31st STREET
KENOSHA, WISCONSIN 53140
PHONE NO.: 1-262-654-3516
FAX NO.: 1-262-654-0803
e-mail: SALES@FAMCOMACHINE.COM