

RL Regular Duty Lead Screw Precision Dovetail Slides



Standard Features

Precision Lead Screw • Graduated Micrometer Dial • Balanced Crank Handle • Thrust Bearings

MODEL	SLIDE WIDTH	CARRIER HEIGHT	SLIDE HEIGHT	AVAILABLE LENGTHS				WEIGHT PER INCH OF CAST IRON	
				CARRIER		BASE		CARRIER	BASE
				MINIMUM	MAXIMUM	MINIMUM	MAXIMUM		
RL-2	2"	.75"	1.125"	2"	36"	2"	60"	.27 lbs.	.28 lbs.
RL-3	3"	.81"	1.250"	3"	36"	3"	60"	.43 lbs.	.50 lbs.
RL-4	4"	1.06"	1.625"	4"	36"	4"	60"	.75 lbs.	.88 lbs.
RL-6*	6"	1.25"	1.875"	6"	36"	6"	72"	1.45 lbs.	1.38 lbs.

* R6 Slides furnished with lubrication ports.

- ▶ 5/16-40 "V" Type Lead Screw on R2 and R3 Slides
 - ▶ 1/2-20 "V" Type or 1/2-10 Acme Lead Screw on R4 Slides
 - ▶ 5/8-20 "V" Type or 5/8-10 Acme Lead Screw on R6 Slides

Accessories

Gib Lock Handles • Way Wipers • Knurled Knob • Accordion Type or Steel Covers
Tapered Gib • Anti-Backlash Nut • Nickel Plating • Compounding • Right Angle Drive



MILWAUKEE
SLIDE AND
SPINDLE

FAMCO MACHINE DIVISION

BELCO INDUSTRIES, INC.

1001-31st STREET

KENOSHA, WISCONSIN 53140

PHONE NO.: 1-262-654-3516

FAX NO.: 1-262-654-0803

e-mail: SALES@FAMCOMACHINE.COM