

## R Regular Duty Basic Precision Dovetail Slides



### Standard Features

Accurate Motion · 26 Standard Models · Easily Adjusted Gibs · Broad Range of Uses  
Designed where the Load Induced into the Assembly is Moderate and Compact Design is Essential

MODEL	SLIDE WIDTH	CARRIER HEIGHT	SLIDE HEIGHT	AVAILABLE LENGTHS				WEIGHT PER INCH OF CAST IRON	
				CARRIER		BASE		CARRIER	BASE
				MINIMUM	MAXIMUM	MINIMUM	MAXIMUM		
R2	2"	.75"	1.125"	2"	36"	2"	60"	.27 lbs.	.28 lbs.
R3	3"	.81"	1.250"	3"	36"	3"	60"	.43 lbs.	.50 lbs.
R4	4"	1.06"	1.625"	4"	36"	4"	60"	.75 lbs.	.88 lbs.
R6	6"	1.25"	1.875"	6"	36"	6"	72"	1.45 lbs.	1.38 lbs.

\* R6 Slides furnished with lubrication ports.

### Accessories

Gib Lock Handles · Way Wipers · Accordion Type or Steel Covers  
Tapered Gib · Nickel Plating · Compounding · Reduced Overall Height



MILWAUKEE  
SLIDE AND  
SPINDLE

## FAMCO MACHINE DIVISION

BELCO INDUSTRIES, INC.

1001-31<sup>st</sup> STREET

KENOSHA, WISCONSIN 53140

PHONE NO.: 1-262-654-3516

FAX NO.: 1-262-654-0803

e-mail: [SALES@FAMCOMACHINE.COM](mailto:SALES@FAMCOMACHINE.COM)