

HW Hardened Steel Way Precision Slides



Standard Features

Designed to Carry Greater Loads than Conventional Dovetail Slides • High Load and Slow Speed
55 to 60 Rc Flame Hardened Rails • Gibs in Keepers • Lubrication to Ways and Drives

MODEL	SLIDE WIDTH	BASE HEIGHT	SLIDE HEIGHT	AVAILABLE LENGTHS				WEIGHT PER INCH OF CAST IRON	
				CARRIER		BASE		CARRIER	BASE
				MINIMUM	MAXIMUM	MINIMUM	MAXIMUM		
HW-7	7"	3.362"	5.000"	7"	38"	7"	50"	2.11 lbs.	2.29 lbs.
HW-9	9"	5.033"	7.000"	9"	57"	9"	110"	3.31 lbs.	4.64 lbs.
HW-12	12"	7.000"	10.000"	12"	57"	12"	110"	7.07 lbs.	8.37 lbs.
HW-15	15"	8.204"	11.500"	15"	61"	15"	110"	9.96 lbs.	12.52 lbs.
HW-18	18"	9.261"	13.000"	18"	67"	18"	110"	13.07 lbs.	16.75 lbs.
HW-24	24"	10.648"	15.000"	24"	85"	24"	110"	20.48 lbs.	23.77 lbs.
HW-32	32"	10.050"	15.000"	24"	24"	32"	110"	33.57 lbs.	34.90 lbs.

Accessories

Servo, Stepper or Other Motor Drives • Air or Hydraulic Cylinder Drives
Ball Screw or Lead Screw Compatible • Drilled, Tapped or Counterbored Mounting Holes
Compounding • Antifriction Turcite Covered Bearing Surfaces • Tapered Gibs
Accordion Type or Steel Way Covers • Way Wipers
Low Profile Slides for Special Needs • Stress Relieved Steel Weldment vs. Cast Iron Base



MILWAUKEE
SLIDE AND
SPINDLE

FAMCO MACHINE DIVISION

BELCO INDUSTRIES, INC.
1001-31st STREET
KENOSHA, WISCONSIN 53140
PHONE NO.: 1-262-654-3516
FAX NO.: 1-262-654-0803
e-mail: SALES@FAMCOMACHINE.COM