

RB-AC/-HC Heavy Duty Recessed Base Air or Hydraulic Cylinder Powered Precision Dovetail Slides



MILWAUKEE
SLIDE AND
SPINDLE



Standard Features

800 P.S.I. Hydraulic and 250 P.S.I. Air Working Pressure • Double Acting Non-Cushioned Cylinders
Hand Flaked Ways • For Quick-Action Movements and Repeatability with High Loads

MODEL	SLIDE WIDTH	CARRIER HEIGHT	SLIDE HEIGHT	AVAILABLE LENGTHS				WEIGHT PER INCH OF CAST IRON	
				CARRIER		BASE		CARRIER	BASE
				MINIMUM	MAXIMUM	MINIMUM	MAXIMUM		
RB-AC/-HC 4	4"	1.62"	2.250"	4"	36"	4"	60"	1.00 lbs.	1.05 lbs.
RB-AC/-HC 6	6"	2.00"	3.000"	6"	36"	6"	72"	2.50 lbs	1.69 lbs.
RB-AC/-HC 8	8"	2.00"	3.250"	8"	36"	8"	72"	3.16 lbs	2.93 lbs.
RB-AC/-HC 10	10"	2.81"	3.750"	10"	36"	10"	72"	4.80 lbs	3.66 lbs.
RB-AC/-HC 12	12"	2.43"	4.000"	12"	36"	12"	72"	5.77 lbs	5.27 lbs.
RB-AC/-HC 16	16"	3.25"	5.000"	16"	60"	16"	100"	9.47 lbs	9.10 lbs.
RB-AC/-HC 20	20"	3.87"	6.000"	20"	60"	20"	100"	14.43 lbs	13.58 lbs.
RB-AC/-HC 24	24"	4.50"	7.000"	24"	60"	24"	100"	20.37 lbs	18.93 lbs.

- 2" Air Cylinder Bore and 1-1/2" Hydraulic Cylinder Bore on RB-4 Slides
- 2-1/2" Air Cylinder Bore and 1-1/2" Hydraulic Cylinder Bore on RB-6 Slides
- 3-1/4" Air Cylinder Bore and 2" Hydraulic Cylinder Bore on RB-8 Slides
- 4" Air Cylinder Bore and 2" Hydraulic Cylinder Bore on RB-10 Slides
- 5" Air Cylinder Bore and 2-1/2" Hydraulic Cylinder Bore on RB-12 Slides
- 6" Air Cylinder Bore and 3-1/4" Hydraulic Cylinder Bore on RB-16 Slides
- 6" Air Cylinder Bore and 4" Hydraulic Cylinder Bore on RB-20 Slides
- 6" Air Cylinder Bore and 5" Hydraulic Cylinder Bore on RB-24 Slides

Accessories

Way Wipers • Accordion Type or Steel Covers • Compounding
Tapered Gib • Nickel Plating • Special Cushioning and/or Valving



MILWAUKEE
SLIDE AND
SPINDLE

FAMCO MACHINE DIVISION

BELCO INDUSTRIES, INC.

1001-31st STREET

KENOSHA, WISCONSIN 53140

PHONE NO.: 1-262-654-3516

FAX NO.: 1-262-654-0803

e-mail: SALES@FAMCOMACHINE.COM